

Material Safety Data Sheet

G1520 – BUILDER NATURAL

Page 1

### Section 1 – Identification of the Substance/Preparation and of the Company/Undertaking

**Product Name: Builder Natural** MSDS# KIG031703-PBC

**Chemical Name:** N/A MSDS Initial Approval 04/07/20 MSDS Prepared **BSO** 03 Date:

GEL Type: Builder Family: UV GELS Manufacturer: CNC International BV

Burgemeesterlaan 2 – 6002 EG Weert - Netherlands Product Use: NAIL GEL Emergency Phone Numbers:+31-495-547409 **Information Contacts:** +31-495-548213 Product#: G1520

#### Section 2 - Composition/Information on Ingredients

Chemical Identity	CAS#	EINECS#	INCI (or other substance) Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen  IARC/NTP/OSHA	%
Polyurethane Acrylate Oligomer	Exempt	N/E	Polyurethane Acrylate Oligomer	N/E	N/E	Not Listed	70-75
Tripropylene Glycol Diacrylate Esters (TPGDA)	42978-66-5	256-032-2	N/E	N/E	N/E	Not Listed	15-20
Ethoxylated Trimethylolpropane triacrylate esters (ETPTA)	28961-43-5	N/DA	N/E			Not Listed	3-5
Silicon Dioxide	60676-86-0	262-373-8	Silica	N/E	N/E	Not Listed	3-5
Hydroxycyclohexyl phenyl ketone	947-19-3	213-426-9	Hydroxycyclohexyl phenyl ketone	N/E	N/E	Not Listed	0-1
Benzophenone	119-61-9	204-337-6	Benzophenone	N/E	N/E	Not Listed	0-1
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	Not Listed	0-1
N/E - None Established N/R - Not Reviewed	N/DA - No D N/A - Not						

Hazard Symbols: Xi Risk Phrases: R22, R36/38, R43 **Safety Phrases:** S18, S24/25, S36/37, S38

#### Section 3 - Hazards Identification

#### **EMERGENCY OVERVIEW**

This information is based on findings from related or similar materials.

May be slightly toxic.

May cause moderate skin injury (reddening & swelling).

May cause chemical burn in eye.

#### Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry No specific information available.

No specific information available. Contains materials that are essentially nonirritating, but contact Eye

may cause slight transient irritation.

No specific information available. Contains materials that may cause moderate skin injury (reddening Skin

and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since

irritation may not occur immediately, contact can go unnoticed.

Ingestion No specific information available. Contains materials that may be practically nontoxic.

Inhalation No specific information available. Low volatility makes vapor inhalation unlikely. Aerosol can be

irritating.

**Sub-Chronic Effects** No specific information available. Limited tests showed no evidence of teratogenicity in animals. A

lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section 11, Toxicological Information for Details

#### Section 4 - First Aid Measures

First Aid for Eye Flush with plenty of water for 15 minutes and seek medical attention.

First Aid for Skin Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

First Aid for Inhalation In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing

has stopped, administer artificial respiration and seek medical attention.

If appreciable quantities are swallowed, seek medical attention. First Aid for Ingestion



#### **Material Safety Data Sheet** G1520 – BUILDER NATURAL Page 2

#### Section 5 - Fire Fighting Measures

Flash Point(°F/°C)	Flammable Limit(vol%)	Auto-ignition Temperature(vol%)
> 212°F/100°C Setaflash	No Data	No Data

**Method:** 

Extinguishing Media: Fire Fighting **Instructions:** 

Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires. Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or

products of combustion exists.

Unusual Hazards: High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can

result in explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream

of water to control fires since frothing can occur.

#### Section 6 - Accidental Release Measures

Spill or Release **Procedures** 

Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb with inert material and dispose of properly. Flush area with water; prevent washings from entering waterways.

#### Section 7 - Handling and Storage

Handling

Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential.

When handling gel for product use, do not heat above 100°F/38°C or disassociation of silica in product may

occur. Material is UV light sensitive, avoid prolonged exposure to light/heat.

Storage Store in a cool place, away from heat and light. Store at temperatures below 100°F/38°C.

High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in **Explosion Hazard** 

explosions and the violent rupture of storage vessels or containers.

#### Section 8 - Exposure Controls / Personal Protective Equipment

**Engineering Controls** 

Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.

#### **Personal Protective Equipment**

General

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

A safety shower and eye wash facility should be readily available.

Eye/ Face Protection Skin Protection

Chemical splash goggles. Contact lenses should not be worn. Impervious gloves (Butyl rubber, Neoprene, and/or Nitrile).

A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be Respiratory Protection

permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

#### Section 9 - Physical and Chemical Properties

Appearance	Odor & Odor Threshold	$_{\mathrm{P}}\mathrm{H}$	Specific Gravity	Viscosity	% Volatile
Clear, viscous liquid	characteristic acrylate odor	NA	(H2O=1): 1.15	N/DA	By Volume : < 0.5

Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure: mmHg	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/A	N/A	@ 20 C:<0.01	No Data	No Data	No Data	Insoluble
Flash Point (°F/°C)			ble Limit 1%)		Auto-ignition Temperature (vol%)		
> 212	> 212°F/100°C Setaflash		Data		No Data		



## **Material Safety Data Sheet**

G1520 – BUILDER NATURAL

Page 3

#### Section 10 - Stability and Reactivity

Stability

Normally Stable

**Hazardous Decomposition Products:** 

Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide.

**Incompatibility (Materials to Avoid):** 

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and string bases.

**Hazardous Polymerization:** 

May occur -- Uncontrolled polymerization may cause rapid evolution of

Heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

**Conditions to Avoid:** 

Storage >100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

#### Section 11 - Toxicological Information

Acute Oral Toxicity	<b>Acute Dermal Toxicity</b>	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
No information available	No information available	No information available	No information available	No information available

Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	N/DA	N/DA

#### Section 12 - Ecological Information

**Ecotoxicological Information** 

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

#### **Chemical Fate Information**

Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated.

Do not allow to enter drinking water supplies, wastewater, or soil.

#### Section 13 - Disposable Considerations

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the genrators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations.

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

#### Section 14 - Transport Information

DOT (49 CFR 172)		
Proper Shipping Name:	Non-Regulated Material	
Identification Number:	N/A	
Marine Pollutant:	No	
Special Provisions:	N/A	
Emergency Response Guidebook (ERG) #:	N/A	
IATA (DGR):		
Proper Shipping Name:	Non-Regulated Material	
Class or Division:	N/A	
UN or ID Number:	N/A	
Packaging Instructions:		
Emergency Response Guidance (ICAO)#:		
IMO (IMDG):		
Proper Shipping Name:	Non-Regulated Material	
Class or Division:	N/A	
UN or ID Number:	N/A	
Special Provisions & Stowage/Segregation:	None	
Emergency Schedule (EmS)#:		
Other Information:	Flash point > 100°C	

#### Section 15 - Regulatory Information



# Material Safety Data Sheet G1520 – Builder Natural Page 4

US Federal Regulations	
Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP and ODS's), as defined
	by the U.S. Clean Air Act:
	Benzophenone (SOCMI Chemical).
	This product does not contain any Class 1 or Class 2 ODS.
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA:
	• NONE
	This product does not contain any substances that are a Priority Pollutant or Toxic
	Pollutant under the CWA.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other
	applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard
	Communication Standard. Its hazards are:
	Immediate (acute) health hazard
	Delayed (chronic) health hazard
	Reactive hazard
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261).
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous
	substances that carry a TPQ.
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 304 as extremely hazardous
	chemical for emergency release notification (" CERCLA" List).
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard
	and is regulated under Section 311-312 (40 CFR 370). Its hazards are:
	Immediate (acute) health hazard
	Delayed (chronic) health hazard
	Reactive hazard
SARA Title III: Section 313:	This product contains no chemicals subject to the reporting requirements of Section 313 of Title III
	of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with
maga di idi ana ara	TSCA premanufacture notification requirements.
TSCA Significant New Use Rule:	None of the chemicals listed have a SNUR under TSCA.

**State Regulations** 

State Heganations	
CA Right-to-Know Law:	Silicone Dioxide CAS#60676-86-0.
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Silicone Dioxide CAS#60676-86-0.
NJ Right-to-Know Law:	Silicone Dioxide CAS#60676-86-0.
PA Right-to-Know Law:	Silicone Dioxide CAS#60676-86-0.
FL Right-to-Know	Silicone Dioxide CAS#60676-86-0.
MN Right-to-Know	Benzophenone CAS #119-61-9, Silicone Dioxide CAS#60676-86-0.

International Regulations					
CDSL: Canadian Inventory	Benzophenone CAS #11-61-9 is on the DSL list. WHMIS = n/da				
(on Canadian Transitional List)	-Camphoroquinone CAS #2767-84-2 is not on the DSL list. WHMIS = n/da				
	Tripropylene Glycol Diacrylate Esters (TPGDA) CAS #42978-66-5 is on the DSL list. WHMIS= n/da				
	Ethoxylated Trimethylolpropane triacrylate esters (ETPTA) CAS# 28961-43-5 is on the DSL list. WHMIS=				
	n/da				
	Silicone Dioxide CAS#60676-86-0 is on the DSL list. WHMIS = n/da				
EINECS: European Inventory:	Builder - Natural				
	HAZARD SYMBOLS: Xi: Irritant				
	• RISK PHRASES: <b>R22:</b> Harmful if swallowed, <b>R36/38:</b> Irritating to eyes and skin				
	R43: May cause sensitization by skin contact.				
	• SAFETY PHRASES: <b>S18:</b> Handle and open container with care, <b>S24/25:</b> avoid				
•	contact with skin and eyes, \$36/37: Wear suitable protective clothing and gloves,				
	S38: in case of insufficient ventilation, wear suitable respiratory equipment.				

**Material Safety Data Sheet** 

G1520 – BUILDER NATURAL

Page 5

\*D

#### Section 16 - Other Information

Hazard Rating System (Pictograms) **HMIS:** NFPA: Health **Flammability Flammability** 2 1 Health Reactivity Reactivity

- Respiratory protection may be necessary depending on conditions of use. Refer to Section VIII of this MSDS for respiratory protection guidelines.

OSHA PEL for nuisance dust: 15 mg/m<sup>3</sup> (total dust)

5 mg/m<sup>3</sup> (respirable dust)

ACGIH PEL for nuisance dust:  $10 \text{ mg/m}^3$ 

Revised Sections since Last Version: Section 2 contents update

D

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable.