

## 1. Product and Company Identification

**Product Name:** Nail Scrub  
**Article Code:** D3000-D3011

**Manufacturer:** CNC International BV  
 Burgemeesterlaan 2  
 6002 EG Weert – The Netherlands

**Emergency Telephone Numbers:** +31 495 547409

## 2. Hazards Identification

### 2.1. Classification of the substance or mixture

#### 2.1.1 Commission Regulation (EC) 1272/2008, as amended

Hazard Classes	Classification
Flammable Liquid	Flam liq. 2, H225
Eye irritant	Eye irrit. 2, H319
Specific target organ toxicity – single exposure	STOT, sing. 3, H336

#### 2.1.2 Most important adverse effects

Product and vapours from product are highly flammable.  
 Vapour and air can form explosive mixtures.  
 Eye irritant.

### 2.2 EC labelling according to Commission Regulation (EC) 1272/2008, as amended

#### 2.2.1 Label elements

Trade Name Nail Scrub

#### 2.2.2 Hazard pictograms



#### 2.2.3 Signal word

Danger

#### 2.2.4 Hazard Statements

H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### 2.2.5 Precautionary statements

##### Prevention

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed

P261 Avoid breathing vapours

### Reaction

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do; continue rinsing.  
P337+P313 Get medical advice/attention if eye irritation persists.

### Storage

P235 Keep cool

### Disposal

P501 Dispose of contents/container to a specialist waste reprocessing plant in accordance with local/regional regulations.

### 2.3 Other hazards

The product does not meet the criteria for PBT or vPvB.

## 3. Composition / Information on Ingredients

### 3.1 Substances

Not applicable

### 3.2 Hazardous Components

INCI – Ingredient Name	CAS Number	EINECS Number	CLP Classification	%-Range
Acetone	67-64-1	200-662-1	Flam. Liq. 2, H225 Eye irrit. 2, H319 STOT, sing. 3, H336	25-100
Isopropyl alcohol	67-63-0	200-661-7	Flam. Liq. 2, H225 Eye irrit. 2, H319 STOT. Sing. 3, H336	25-100

For the full text of the hazard statements mentioned in sections 2 and 3 see section 16.

## 4. First Aid Measures

### 4.1. Description of first aid measures

**Skin contact:** Take off contaminated clothing.

**Inhalation:** Move person into fresh air and keep at rest. Call a doctor/physician if the person feels unwell.

**Ingestion:** Rinse mouth. Consult a doctor/physician if the person feels unwell.

**Eye Contact:** Rinse the eyes with water for several minutes; remove contact lenses, if present and easy to do; continue rinsing. Get medical advice/attention if eye irritation persists.

### 4.2 Most important symptoms and effects, both acute and delayed:

#### 4.2.1 Acute symptoms and effects on exposure

On contact with the fluid: red eyes and pain. On inhalation: sleepiness or drowsiness.

#### **4.2.2 Delayed symptoms and effects on exposure**

On repeated and/or long-term exposure: dry or cracked skin.

## **5. Fire Fighting Measures**

### **5.1. Extinguishing media**

**Extinguishing media:** Powder, foam, water spray, carbon dioxide.

### **5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** Vapour and air forming explosive mixtures.  
In the event of fire, toxic vapour will be released (carbon monoxide and/or carbon dioxide).

### **5.3. Advice for fire-fighters**

#### **5.3.1 Protective measures**

In the event of fire: keep containers in the immediate vicinity cool by spraying with water.

#### **5.3.2 Special protective equipment**

Wear self-contained breathing apparatus when approaching the fire or when in a room if necessary.

## **6. Accidental Release Measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Gloves, boots. Respiratory equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.

### **6.2 Environmental precautions**

Keep away from drains, surface water or soil.

### **6.3 Methods and material for containment and clearing up**

Absorb small spillages of product with an inert material. Allow to evaporate in a safe place.  
Large spillages should be dammed off and removed with an explosion-proof vacuum cleaner; recycle where possible. Wash away any residue with water.

### **6.4 Reference to other sections**

See also sections 8 and 13.

## **7. Handling and Storage**

### **7.1. Precautions for safe handling**

Use in well-ventilated areas only.  
Keep away from sources of ignition - No smoking.  
Use explosion-proof electrical equipment and lighting.

### **7.2 Conditions for safe storage, including any incompatibilities**

#### **7.2.1 Preventing fire and explosion**

Keep packaging in a well-ventilated place.  
Keep packaging tightly closed.  
Keep in a fire-resistant place separate from oxidants.

### 7.2.2 Protection against environmental attack

Protect against heat and direct sunlight.  
Suitable materials for packaging: approved plastic/glass/steel/stainless steel.

### 7.3 Specific end use(s)

Please contact the supplier.

## 8. Exposure Controls / Personal Protection

### 8.1. Control parameters

#### 8.1.1 Exposure limit values

<b>Acetone</b>	mg/m <sup>3</sup>	ppm	Indicative
TWA limit value (NL) 8 hours	1,210	500	
TWA limit value (NL) 15 hours	2,420		

<b>Isopropyl alcohol</b>	mg/m <sup>3</sup>	ppm	Indicative
TWA limit value (NL) 8 hours	500		
TWA limit value (NL) 15 hours	1,000		

### 8.2. Exposure controls

#### 8.2.1 Technical measures

Sealed equipment  
Ventilation and local extraction

#### 8.2.2 Individual protective measures

**Respiratory protection:** Respirator with a filter for organic vapour (filter type A).

**Eye protection:** Safety goggles.

**Skin protection:**

**Hands:**  
Butyl rubber 0.7 mm gloves  
Linear low-density polyethylene (LLDPE) 0.75 mm gloves

**Other measures:**  
Protective clothing

#### 8.2.3 Environmental exposure controls

Remove contaminated air from the local extractor and drain waste water in accordance with local environmental regulations.

## 9. Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

<b>Form:</b>	Fluid
<b>Colour:</b>	Blue
<b>Odour:</b>	Distinctive
<b>Odour threshold, mg/m<sup>3</sup></b>	0.4-3

## Material Safety Data Sheet

## D3000-D3011 – Nail Scrub

Page 5

Ph:	Not applicable
Melting point/range, °C	< -20
Boiling point/range, °C	56-82
Flash point, °C	<0
Evaporation rate	Not available
Flammability limits, vol% in air	2.1 - 13 (acetone)
Vapour pressure, mbar at 20 °C	247 (acetone)
Relative density (water = 1)	0.8
Solubility in water	100%
Auto-ignition temperature	425 (isopropyl alcohol)

### 9.2 Other information

Miscibility: Miscible with organic solvents

## 10. Stability and Reactivity

### 10.1. Reactivity

Reactivity: No hazardous reaction if directions for handling and storage are observed.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Reacts strongly to oxidants and strong acids

### 10.4. Conditions to avoid

Conditions to avoid: Storage temperatures >40 °C. Sources of ignition (open flame, warm surfaces and sparks).

### 10.5. Incompatible materials

Materials to avoid: Oxidants and strong acids. Attacks rubber and many synthetics.

### 10.6. Hazardous decomposition products

Haz. decomp. Products: Does not decompose if used and stored as directed.

## 11. Toxicological Information

### 11.1. Acute toxicity

#### Acetone

Acute Toxicity:	LD50	LC50/4 h
Oral	5.8-8.4 mg/kg	
Dermal	> 15.700 mg/kg	
Inhalation		76 mg/l Eye

Serious eye injury/irritation: Irritant

STOT – single exposure: May cause drowsiness or dizziness

#### Isopropyl alcohol

Acute Toxicity:	LD50	LC50/4 h
-----------------	------	----------

Oral	4,396 mg/kg	
Dermal	12,870	
Inhalation		72,6 mg/l Eye

**Serious eye injury/irritation:** Irritant

### 11.2 Symptoms/routes of exposure

The product can enter the body by inhalation of the vapours or swallowing the fluid.

### 11.3 Chronic toxicity

The fluid may cause skin dryness or cracking.

## 12. Ecological Information

### 12.1 Ecotoxicity

#### Acetone

<b>Fish</b>	LC50 fish, 96 hours: 5,540-13,000 mg/l
<b>Crustaceans</b>	LC50 daphnia, 48 hours: 7,635-15,800 mg/l
<b>Algae</b>	LC50 (algae, 72 hours): no data available

#### Isopropyl alcohol

<b>Fish</b>	LC50 fish, 96 hours: 1,400 mg/l
<b>Crustaceans</b>	LC50 daphnia, 48 hours: 7,550-13,299 mg/l
<b>Algae</b>	LC50 (algae, 72 hours): > 1,000 mg/l

### 12.2 Persistence and degradability

The product is easily biodegradable

### 12.3 Bioaccumulative potential

Bioconcentration factor (BCF): Acetone 1; Isopropyl alcohol 3.

Log P octanol/water: Acetone - 0.2; Isopropyl alcohol 0.1.

No significant potential for bioaccumulation (BCF < 500 and log P octanol/water < 4).

### 12.4 Mobility in soil

The product is highly mobile in soil.

KoC coefficient: Acetone 0.6; Isopropyl alcohol ≤25.

### 12.5 Results of PBT and vPvB assessment

The product has been assessed as containing no substances that can be viewed as PBT or vPvB substances.

### 12.6 Other adverse effects

The product is mildly harmful to water.

German hazard codes for water (WGK): Acetone 1; Isopropyl alcohol 1.

## 13. Disposal Considerations

### 13.1 Waste treatment methods

#### Product

Dispose of to a registered incineration plant for solvents, or as hazardous waste in accordance with local regulations. Do not dispose of the product in residual household waste. Prevent the waste product reaching sewers.

#### Contaminated packaging

Treat contaminated empty packaging as hazardous waste.

Treated packaging may be reused.

#### Other safety information

European list of waste (EURL): 07 01 04

## 14. Transport Information

#### Road Transport:

Technical name: : Flammable liquids, N.E.G. (Acetone, Isopropyl alcohol) 3, PGII

Class : 3

Pack Group : II

UN Number : 1993

#### Other Safety information

Hazard label(s) : 3

Tunnel category : (D/E)

Hazard identification nr: 33

Transport category : 2

Limited quantity (LQ) : 1 L

Exempted quantity : E2

## 15. Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Additional national regulations must be observed.

### 15.2 Chemical safety assessment

The product has not been assessed for chemical safety

## 16. Other Information

### 16.1 Key changes since last version

Application of the terms of Regulation (EC) No. 453/2010.

### 16.2 Glossary of abbreviations and acronyms

CAS Chemical Abstracts Service (Division of the American Chemical Society)

CLP Classification, Labelling and Packaging

EC50 Effect Concentration, 50 percent (concentration at which 50 per cent of animals show a particular effect)

EC European Community

IC50 Inhibitory Concentration, 50 percent (concentration at which 50 per cent of algae show

Initial Date: 1-10-2015

	growth inhibition)
LC50	Lethal Concentration, 50 percent (concentration at which 50 per cent of animals die)
LD50	Lethal Dose, 50 percent (dose at which 50 per cent of animals die)
PBT	Persistent, Bioaccumulative and Toxic
Ppm	Parts per million
TWA	Time Weighted Average
vPvB	very Persistent and very Bioaccumulative

**DISCLAIMER**

While CNC International BV believes that the data contained herein are accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which CNC International BV assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data information must be determined by the user to be in accordance with applicable Federal, State and local laws regulations.

CNC International BV requires all Customers who receive this Security Data Record to study it carefully in order to be informed of any dangers presented by the product. As far as security is concerned, the Customer should:

- Inform his employees, agents and sub-contractors of information contained in this form.
- Supply one copy of this form to each one of his own Customers for this product.
- Ask for these same Customers to inform in turn their own Employees and Customers.