

Page 1

Version: 17/08/2005

#### 1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

Trade name Nail Polish

Manufacturer:

Company: CNC International BV Addressee: Burgemeesterlaan 2

6002 EG Weert

Netherlands

Phone +31-495-547409 Fax +31-495-548213

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

This product is considered dangerous and contains the following hazardous substances:

<u>Name</u>	<u>%</u>	Index CEE	Cas	<u>Einecs</u>	Symbol(s)	Phrase(s) R
Toluene	> 10 < 20	601-021-00-3	108-88-3	203-625-9	Xn F	11-38-48/20- 63-65-67
Ethyl Acetate	> 20 < 30	607-022-00-5	141-78-6	205-500-4	Xi F	11 36 66 67
n-Butyl Acetate	> 10 < 20	607-025-00-1	123-86-4	204-658-1		10 66 67
Nitrocellulose	> 10 < 20		9004-70-0	263-069-9	F Xi	11 36/37/38
Propane-2-ol	> 2 < 5	603-117-00-0	67-63-0	200-661-7	Xi F	11 36 67
May contain the following: See section 16 for additional compounds						

| May contain the following: See section 16 for additional compounds

#### 3. HAZARDS IDENTIFICATION

Risk Phrases Highly flammable. May cause harm to unborn child.

Harmful by inhalation and ingestion

Irritant for eyes and skin

May cause lung attack by ingestion

Repeated exposure may cause drowsiness or cracking.

Vapours may cause drowsiness and dizziness



Page 2

Version: 17/08/2005

Primary route of exposure Skin c

Skin contact, inhalation of vapours

#### 3. HAZARDS IDENTIFICATION (CONTINUED)

Symptoms associated with use:

**Inhalation :** Possible drowsiness and dizziness.

Risk of respiratory problems.

**Skin contact:** Redness, pain. The skin absorbs part of the ingredients of this product.

Can cause dry or chapped skin.

**Eye contact:** Redness, watering, blurred vision. Risk of irritant effect on eyes.

**Ingestion:** Risk of lung attack. Health risk even in small quantities. Product

should not come into contact with foodstuffs.

#### 4. FIRST AID MEASURES

In general, in case of doubt or if symptoms persist, consult a physician and show the product label or this MSDS. Never give anything by mouth to a person who is unconscious or likely to become so (state of shock, etc ...)

**Inhalation:** Move to fresh air, keep warm and get medical advice.

If breathing is irregular or stops, give artificial respiration (if possible give

oxygen) and contact the local Emergency Services.

**Skin** Remove soiled clothing, clean affected areas with copious amounts of soapy

contact: water.

Do not use solvents (thinners ...).

**Eye contact:** In case of contact with eyes, rinse immediately with fresh water for 15

minutes holding eyelids open.

Refer the victim to an ophthalmologist immediately and show the product label or this MSDS; this should be treated as an emergency in case of

symptoms (redness, pain, visual problems).

**Ingestion:** If quantity is small (less than a mouthful), rinse mouth with water. DO NOT

induce vomiting. In all cases, seek medical attention.



Page 3

Version: 17/08/2005

#### 5. FIRE-FIGHTING MEASURES

Extinguishing media:

- for minor fires: Chemical powders, carbon dioxide and other extinguishing gases may

be suitable for minor fires.

- recommended: Special foam for polar liquids.

- to avoid: Water without additives.

**Prevention:** Avoid naked flames or other sources of ignition in areas where product

is used; protect electrical equipment (risk of explosive zones). No

smoking.

Dry residue stay highly flammable (contain nitrocellulose)

**Special** Exercise caution when fighting any chemical fire. Use water to keep the

**procedure:** containers exposed to fire cool.

Avoid increase in pressure causing the release of the drum lid. Fire often produces a dense black smoke; vapours heavier than air; exposure to decomposition products constitutes a serious health hazard.

Do not inhale smoke.

Prevent fire-fighting effluent from entering drains, watercourses and/or

environment.

**Special** Self-contained breathing apparatus to protect against toxic gases

**equipment:** produced by thermal decomposition.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal** Remove all possible sources of ignition and thoroughly ventilate

**precautions:** premises.

Do not inhale fumes. Avoid skin and eye contact. See Sections 7 et 8.

**Environmental** Prevent product from entering drains or watercourses.

**precautions:** If product contaminates ground water, rivers or drains (or is likely to do

so), notify the relevant authorities, following the statutory procedures.

Clean up any spills as soon as possible, using a non-combustible

taking up: absorbent material to collect it, for example: sand, earth, vermiculite,

diatomic earth.

Collect material into suitable drums for disposal in accordance with



Page 4

Version: 17/08/2005

regulations (see Section 13).

It is preferable to clean with detergents, do not use solvents.

#### 7. HANDLING AND STORAGE

**General**: Handle in accordance with good industrial hygiene and safety

procedures. Avoid naked flames or other sources of ignition in areas

where product is used. No smoking.

Do not allow unauthorized persons into areas where product is used.

Precautions in handling and storage:

Handle empty containers with care because residual vapours are

flammable. Dry residue stay highly flammable (contain nitrocellulose)

Technical protective measures:

Provide proper grounding. Use only non-sparking tools. Do not use compressed air to either agitate or transfer the contents of storage containers (tanks) / shipping drums containing this material

Avoid build-up of static charges by:

Ø ensuring that flooring is conductive and keeping it clean,

Ø ensuring that equipment in earthed during transfer or stirring of the product or preparations containing the product,

Ø the use of antistatic shoes, clothing and packaging.

Fumes are heavier than air and they may spread at ground level and

form explosive mixtures with air.

Avoid the formation of explosive concentrations and concentrations

above occupational exposure limits.

**Storage:** Store in tightly closed containers in a cool, dry, well-ventilated place,

away from sources of ignition.

**Handling**: Ensure prompt removal from eyes, skin and clothing.

Recommended equipment and procedures:

For personal protection, see Section 8.

Observe the precautions indicated on the label as well as workplace

safety rules.

Wash hands and other exposed areas with mild soap and water before

eat, drink or smoke and when leaving work.



Page 5

Version: 17/08/2005

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values:TLVPELToluene100 ppm150 ppmEthyl Acetate400 ppm-

Butyl Acetate 150 ppm Isopropyl Alcohol 5mg/m3 -

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

**Respiratory** If vapour concentrations exceed the established exposure limits,

**protection:** respiration protection is necessary, wear a gas mask with appropriate

cartridge.

**Eye protection:** Use eye protection (chemical goggles or safety glasses) to avoid

splashing.

**Hand protection:** Use gloves to prevent skin contact and possible irritation.

**Ingestion:** When using, do not eat, drink or smoke.

**Personal hygiene:** Minimize breathing of vapour. Avoid prolonged contact with skin. Wash

hands and other exposed areas with mild soap and water before eat, drink

or smoke and when leaving work.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Liquid, viscous.

Odour:Solvent.Color:VariableBoiling Point/Range (°C):> 77 °CFlash Point (°C):< 21 °C

Explosive Limits % Vol:lowerupperToluene1,27,8Ethyl Acetate2,111,5Butyl Acetate1,27,5Isopropyl alcohol212,7

**Specific gravity:**  $0.95 - 1.05 \text{ gr/cm} 3 \text{ at } 20 \text{ }^{\circ}\text{C}$ 

Solubility in water: Not miscible. Viscosity at 25°C (mpas): Variable



Page 6

Version: 17/08/2005

#### 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

**Conditions to be avoided:** Heating

Materials to avoid: Alkali metals, strong acids/alkalis, fluorine, hydrides, strong

oxidizing agents, water with air and light

**Hazardous decomposition:** Thermal decomposition may liberate carbon and nitrogen oxides

**Further Information** Light sensitive, sensitive to air; unsuitable working materials:

various plastics

Explosible with air in a vaporous/gaseous state

#### 11. TOXICOLOGICAL INFORMATION

Exposure to levels above the values under Section 8, or regular exposure even if levels are lower, of vapours from solvents present in the preparation may be harmful for health; the effects through inhalation of the vapours and/or contact with skin on long or short time are:

Ø irritation of mucous membranes and respiratory tract, renal, liver and central nervous system affections.

Symptoms include headaches, dizziness, fatigue, muscular asthenia and, in extreme cases, unconsciousness.

Prolonged or repeated skin contact can lead to defatting, provoking non-allergic contact dermatitis and absorption of product through the skin.

Splashes to the eyes can cause irritation and irreversible damage (possibility of lesions of at least 24 hours' duration).

Depending on the shade, varnishes may contain traces of one or more of the following metals, in the form of salt and/or oxides, present in the pigments used: aluminium, barium, calcium, cobalt, chromium, copper, iron, magnesium, titanium. In principle, these elements are not dangerous, but there is a slight risk of sensitisation for susceptible persons.

#### 12. ECOLOGICAL INFORMATION

Ecotoxic effects: Biological effects: toxic effect on fish and plankton. Risk of formation of explosive vapours above water surface.



Page 7

Version: 17/08/2005

Fish toxicity (LC50)

Specific to solvents

**Bacteria toxicity (LC50):** 

Do not allow to enter waters, waste water, or soil!

#### 13. DISPOSAL CONSIDERATIONS

**Material** Avoid release to the environment.

**disposal:** Dispose of this material at hazardous or special waste collection point or

give to an agreed waste collector / transporter for elimination or treatment.

Dispose in a safe manner in accordance with local regulations.

**Container:** Empty containers /drums for storage or transport before giving to an agreed

collector. Keep label (Flame, Class 3) on the container and dispose of it as

hazardous waste.

#### 14. TRANSPORT INFORMATION

Proper shipping name	Paint related mater	ial UN:	1263
ADR/RID:	22	A DD/DID	2
H.I.: Pookoging Croup	33 II	ADR/RID:	3
Packaging Group IMDG	11		
IMCO:	3	EMS	3-05
<b>Packaging Group</b>	II	Flashpoint	- 4 °C
IATA/IACO			
ICAO Label:	Flammable liquid	Packaging Group	II

#### 15. REGULATORY INFORMATION

Symbols Harmful Xn Highly flammable F

R Phrases R11 Highly flammable R36/38 Irritant to eyes and skin

R48/20 Harmfull: repeated exposure by inhalation may cause serious

effects for health

R63 Possible risks of harm to the unborn child R65 Harmfull: ingestion may cause lungs attack

R66 Repeated exposure may cause skin dryness or cracking.



### MATERIAL SAFETY DATA SHEET

Page 8

NAIL POLISH Version: 17/08/2005

	R67	Vapours may cause drowsiness and dizziness.
S Phrases	<b>S</b> 9	Keep container in a well-ventilated place
	S16	Keep away of sources of ignition - No smoking
	S26	In case of contact with eyes, rinse immediately with plenty of
		water and seek medical advice
	S27	Take off immediately all contaminated clothing
	S29	Do not empty into drains
	S33	Take precautionary measures against static discharges
	S37/39	Wear protective gloves and eye/face protection.
	S43	In case of fire, use special foam for polar liquids or chemical

#### 16. OTHER INFORMATION

#### MAY CONTAIN THE FOLLOWING COMPOUNDS:

INCI Name	Cas	<u>Einecs</u>
Acetyl Tributyl Citrate	77-90-7	203-067-0
Isopropyl Alcohol	67-63-0	200-661-7
Stearalkonium Hectorite	94891-33-5	-
Camphor	76-22-2	200-945-0
Acrylates Copolymer	25035-69-2	-
Benzophenone - 1	131-56-5	205-029-4
Panthenol	81-13-0	201-327-3
Tosylamide/Formaldehyde resin	25035-71-6	-
P.A.T.A.G.C. (Phthalic Anhydride/ Trimellitic Anhydride/ Glycols Copolumer	-	-
Benzophenone – 3	131-57-7	205-031-5
Dimethicone	9016-00-6	-
Oenethera Biennis (evening primrose) oil	-	-
Polyethylene Terephthalate	25038-59-9	-
Mica & CI 77891 & CI 19140 & CI 42090 & Hydrogenated	12001-26-2	-



### MATERIAL SAFETY DATA SHEET

Page 9

NAIL POLISH Version: 17/08/2005

Polyisobutene		
Silica & Aluminium Powder & CI	7631-86-9	-
77491		
Mica & CI 77891 & CI42090 & Hydrogenated Polyisobutene & Palmitic Acid	12001-26-2	
Calcium Aluminium Borosilicate & Silica & CI 77891	-	-
Synthetic Fluorphlogopite & CI 77491	-	-
Mica& CI 77891 & CI77510 & CI 77499	12001-26-2	-
Mica & CI 77891 & CI 77491	12001-26-2	-
Mica & CI 77491	12001-26-2	
Mica & CI 77499	12001-26-2	
Mica & CI 77891	12001-26-2	-
Mica & CI 77491 & CI 77891 & 77510	12001-26-2	-
Mica & CI 77891 & CI 77510 & CI75470	12001-26-2	-
Mica & CI 77491 & CI 77891 & 77499	12001-26-2	-
Mica & CI 77891 & CI 77491 & CI 77499	12001-26-2	-
Mica & CI 77499 & CI 77891	12001-26-2	-
Mica 77891 & CI 77288	12001-26-2	-
CI 77491 & Silica	-	-
Silica & CI 77000 & CI 77491	7631-86-9	-
Mica & CI 77891 & CI 77861	12001-26-2	-
CI 77163	7787-59-9	232-122-7
CI 77491	1309-37-1	215-168-2
CI 19140	1934-21-0	235-428-9
CI 15850	5858-81-1	227-497-9
CI 77510	14038-43-8	237-875-5



### MATERIAL SAFETY DATA SHEET

Page 10

NAIL POLISH	Version: 17/08/2005

CI 60725	81-48-1	201-353-5
CI 77000	7429-90-5	231-072-3
CI 15850:1	5281-04-9	226-109-5
CI 15850	5858-81-1	227-497-9
CI 15880	6417-83-0	229-142-3
CI 42090	53026-57-6	272-939-6
CI 74160	147-14-8	250-685-1
CI 77499	1309-37-1	215-168-2
CI 77510	14038-43-8	237-875-5
CI 77266	1333-86-4	215-609-9
CI 77891	13463-67-7	236-675-5
CI 19140	12225-21-7	235-428-9
CI 73360	2379-74-0	219-163-6
CI 15880	6417-83-0	229-142-3

The contents and format of this MSDS are in accordance with EEC Commission Directive 93/112/EEC.

DISCLAIMER OF LIABILITY The Information contained in this MSDS was obtained from sources, which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Department issuing data specification sheet: EHS Department Approved: Laboratory

End of document